



WHEN IS ISS THE RIGHT CHOICE OVER DREDGING?

OCT 22
2025



SMWG
Sediment Management Work Group

Introductions



Rory Kilkeny, PE
ENTACT
Principal Geotechnical
Engineer



Mike Sabulis
GEI
Vice President



Ben Gezon
ENTACT
Sediment Practice Lead





Trae Deri
Geo-Solutions
Project Manager



ISS and Sediment Remediation

- Goal: Reduce hydraulic conductivity to reduce/eliminate contaminant migration
- End product is an improved soil/sediment with reduced hydraulic conductivity and higher geotechnical strength
 - HC: 1×10^{-6} cm/sec: negotiable based on geology
 - UCS: 50 psi: negotiable based on endpoint use.
- Solidification is physical not chemical (i.e. stabilization)
- Dredging and capping may still be necessary!



□ Site Attributes Advantageous for ISS

- High waste disposal costs
- Adjacent to critical infrastructure
- ISS treatment thickness > 4 feet
- Treatment volumes > 10,000 CY



Water Conditions

- Water Flow and Current
 - » Water velocity
 - » Barge maneuverability
 - » Silt curtain and containment boom effectiveness
- Water Column Depth
 - » Minimum draft
 - » Tidal fluctuations
 - » Equipment limitations
 - » Volumetric expansion freeboard




Working Restrictions

- Access
 - » Bridge clearances
 - » Upland support areas/batch plant
 - » Marine traffic
 - » Launch site access and proximity
- Structures
 - » Bridge abutments, bulkheads, piers/piling
 - » Overhead and subsurface utilities



□ Marine Logistical Considerations


- Barge Design and Positioning
 - » Maximize columns per move
 - » Ballast and draft constraints
 - » Can the batch plant be on shore?
- Debris Management
 - » Pre-investigation – limited usefulness
 - » Support barges



Marine Logistical Considerations

1697800 Y

- Swell Management
 - » Sequencing
 - » Equipment flexibility
 - » Headspace for restoration cap



1697400 Y

Approximate Material Remaining 03302020 Dredge Base.mtd		
Date	CY Removed	
04/06/2020	564.0	
04/07/2020	1421.6	
04/08/2020	497.2	
04/09/2020	906.1	
04/10/2020	1140.5	
Total Material Material Removed To Date	9698.5*	

773200 X




Managing Surface Water


- Turbidity / Sheen / pH
 - » Turbidity Curtains
 - » Moonpools
 - » Cofferdams
 - » Washout controls
- Mixing Methodology
 - » Spinning down
 - » Lower RPMs at surface mixing



ISS Regulatory Challenges

- Early & proactive stakeholder engagement is critical
 - Diverse concerns & priorities
 - Educating communities of advantages
 - Secure riparian rights & coastal conveyance agreements
- Performance Standards
 - Hydraulic Conductivity: primary metric
 - UCS: secondary metric to meet project strength requirements
 - Leachability: Utilize bench scale if needed, not appropriate for full scale.
- Long term monitoring
 - Similar to cap monitoring requirements
 - Limited info for sediment ISS projects





 **OPEN FORUM**

